

## TECHNICAL INFORMATION

### Physical properties

Total Weight: 460g/m<sup>2</sup> (nominal)  
Vinyl Weight: 370g/m<sup>2</sup> (nominal)  
Substrate Type: Polyester/Cellulose Nonwoven  
Substrate Weight: 90g/m<sup>2</sup> (nominal)

### This product meets type II specification

Tensile Strength: MD 80 N/cm (nominal)  
TD 60 N/cm (nominal)  
Tear Strength: 8500 mN (nominal)

### Roll size:

Made to order.  
Produced in bespoke panels or running metres.

### Pattern Repeat

Refers to design.

### Fire Rating:

Class B when bonded  
To a suitable substrate  
(Class A2 – s1,d0 or better)  
Class A ASTM E-84 tunnel test

### Adhesive:

Newmor Heavy.  
Varies with substrate - please enquire.

### Bacteria Resistance:

Contains an active Fungicide.

### Light Fast:

Excellent Light Fastness  
BS EN ISO 105-B02 7/8

### Light reflective value (LRV)

Available on request.  
In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

### Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WA – Quality Standard W-101.

### Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.  
Resistant to temporary staining of oils, fats, mild acids and alkalis.

### Quality Assurance:

Our management systems and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

### Availability:

Made to order, lead times available upon request.

### Origin:

Designed, coloured, manufactured and stocked in the UK.

### Warranty:

Newmor offers a five year warranty against manufacturing defects.  
Full details available on application.

### Samples:

Larger samples are readily available on request.

### Maintenance:

Refer to full Digital Cleaning and Maintenance instructions, available upon request or download from the Newmor website.



This product contains at least 20% recycled material